

# WEM-D048/03-FS00FD

## Connector with cables Information

No	P/N	Head	Purpose of use / specification	End	Remark
		Housing Crimp		Housing Crimp	
1	WEM-PO-CO-CA-100	M.105307-1203	<b>Main Power</b> connector with cables, 1m UL2464 AMSB 20AWG 3C (No shield)	Open	WE2A 05A-PO 공용
		M.105300-2100			
2	WEM-MO-CO-CA-100	M.105307-1204	<b>Motor UVW</b> connector with cables, 1m UL2464 AMSB 20AWG 4C (No shield)	Open	WE2A 05A-MO 공용
		M.105300-2100			
3	WEM-DE-CO-CA-100	M.505565-1501	<b>Digital Encoder</b> connector with cables, 1m UL2464 AMSB 26AWG 8PR (Shield)	Open	WEMH-DE 공용
		M.505431-1000			
		M.505431-1100			
4	WEM-AE-CO-CA-100	M.505565-1401	<b>Analog Encoder</b> connector with cables, 1m UL2464 AMSB 26AWG 8PR (Shield)	Open	
		M.505431-1000			
		M.505431-1100			
5	WEM-SE-CO-CA-100	M.505565-0801	<b>Serial Encoder</b> connector with cables, 1m UL2464 AMSB 26AWG 4PR (Shield)	Open	WEMH-SE, WE2S-SE 공용
		M.505431-1000			
		M.505431-1100			
6	WEM-IO-CO-CA-100	M.505565-1001	<b>GPIO</b> connector with cables, 1m UL2464 AMSB 26AWG 10C (Shield)	Open	WE2S-APS, WEMH-IO, WE2A 05A-IO 공용
		M.505431-1000			
		M.505431-1100			
7	WEM-ECAT-CO-CA-100	M.505565-0501	<b>EtherCAT &amp; RJ45</b> connector with cables, 1m CAT7 S/FTP 26AWG 4PR (LAN)	RJ45	WEMH-ECAT, WE2A 05A-ECAT 공용
		M.505431-1000			
		M.505431-1100			
8	WEM-CAN-CO-CA-100	M.505565-0301	<b>CAN</b> connector with cables, 1m UL2464 AMSB 26AWG 3C (Shield)	Open	WE2A 05A-CAN 공용
		M.505431-1000			
		M.505431-1100			
9	WEM-DE2-CO-CA-100	M.505565-1501	<b>Digital encoder2</b> connector with cables, 1m UL20276 AMSB 28AWG 10PR (Shield)	M.51353-1600	변환보드 연결 케이블 (WEM전용)
		M.505431-1000		M.56134-9000	
		M.505431-1100			
10	WEM-ECAT2-CO-CA-100	M.505565-0501	<b>ECAT &amp; ECAT</b> connector with cables, 1m AWM2517,IMOEXV-SB-P3,AWG26,2PR (Shield)-가동형 UL2464 26AWG 2PR(Shield)-비가동형	M.505565-0501	Drive와 Drive를 연결하는 EtherCAT 통신 케이블, 1m
		M.505431-1000		M.505431-1000	
		M.505431-1100		M.505431-1100	
11	WEM-ECAT2-CO-CA-030	M.505565-0501	<b>ECAT &amp; ECAT</b> connector with cables, 30cm AWM2517,IMOEXV-SB-P3,AWG26,2PR (Shield)-가동형 UL2464 26AWG 2PR(Shield)-비가동형	M.505565-0501	Drive와 Drive를 연결하는 EtherCAT 통신 케이블, 30cm
		M.505431-1000		M.505431-1000	
		M.505431-1100		M.505431-1100	

※ M. = MOLEX

※ Cable은 별도 구매 품목, 가격은 대리점 문의, ECAT2 케이블은 가동형만 재고 보유하고 있습니다, 비가동형은 별도 문의

※ 100개 이하 샘플은 100Cm (1m) Shield cable로 판매, 1m Cable 기준 발주서 접수시 7일 이내 공급 가능

※ 길이 100Cm (1m)Shield Cable 외 날선 및 기타 길이 (30Cm, 200Cm, 300Cm....) 등은 100개 이상 주문시 공급 가능.

※ 상기 커넥터 및 케이블 정보는 편집과정에서 오류가 발생 할 수 있으니 H/W Manual에서 반드시 확인하시기 바랍니다.